

BATTERY SEPARATOR, ITS MANUFACTURE AND ALKALINE SECONDARY BATTERY

BATTERY SEPARATOR, ITS MANUFACTURE AND ALKALINE SECONDARY BATTERY

Patent Number: JP8185848
Publication date: 1996-07-16
Inventor(s): KAMISAKA MASARU; TADOKORO YOSHIYUKI
Applicant(s):: ASAHI CHEM IND CO LTD
Requested Patent: ☐ JP8185848
Application Number: JP19940337689 19941228
Priority Number(s):
IPC Classification: H01M2/16 ; D04H1/48 ; D06M13/17 ; D21H13/26 ; H01M10/24
EC Classification:
EC Classification:
Equivalents:

Abstract

PURPOSE: To provide a battery separator with high mechanical strength and high electrolyte retention factor, manufacturing method for the separator, and an alkaline secondary battery excellent in cycle characteristic, using this separator.

CONSTITUTION: In a wet process nonwoven fabric in which at least one kind of thermoplastic short fibers and heat bonding short fibers are three-dimensionally entangled each other by water stream, part or whole of the heat bonding short fibers is melted to bond fibers, 0.05-0.5wt.% nonionic surface active agent based on the total weight of the nonwoven fabric is attached on the surface of the fibers. A battery separator obtained has a speed of liquid absorption of 40mm or more and an electrolyte retention factor of 85% or more, and it is preferably manufactured in such a way that water stream is struck against a mixed sheet comprising at least one kind of thermoplastic short fibers and heat bonding short fibers, produced in a paper machine process to three-dimensionally entangle these fibers, part or whole of the heat bonding short fibers is melted by heat treatment to obtain a nonwoven fabric, then 0.05-0.5wt.% nonionic surface active agent based on the total weight of the nonwoven fabric is attached on the surface of the nonwoven fabric.

Data supplied from the esp@cenet database - I2

SEPARATOR FOR ALKALINE SECONDARY BATTERY